

MATERIAL SAFETY DATA SHEET**150 ACRYLIC LATEX**

SUPPLIER Mer-Krete Systems, a division of ParexLahabra
501 S. Van Ness Avenue
Torrance, CA 90501

CONTACT Gary Linza
PHONE 310.320.1880
DATE 08.25.99

INGREDIENTS

Styrene/Butadiene Polymer
Water

CAS NUMBER

9003-55-8
7732-18-5

OSHA

N/A
N/A

ACGIH

N/A
N/A

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point - 100C Freezing Point - 0C Vapor Density - 17.5 @ 20C Specific Gravity - 1.00
Solubility in Water - Soluble in all proportions Appearance - Milky white liquid Odor - Sweet smelling

FIRE & EXPLOSION HAZARDS

Flash Point - N/A Special Fire Fighting Procedures - Wear self-contained breathing apparatus.
Unusual Fire & Explosion Hazards - Black smoke, noxious gases may be generated if material ignites after water boils off.

REACTIVITY DATA

Stability-Stable Materials to Avoid - None Hazardous Decomposition or Byproducts - None
Hazardous Polymerization - Will not occur

HEALTH HAZARD DATA

Routes of Entry - Inhalation, Skin Contact, Eye Contact, Ingestion
INHALATION - May cause irritation of the nose and throat.
SKIN CONTACT - Prolonged or repeated exposure may cause slight skin irritation.
EYE CONTACT - May cause pain and irritation depending on duration of contact.
INGESTION - May cause nausea, vomiting, abdominal pain. Toxicity is considered to be low.

First Aid Procedures

INHALATION - Remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen. Contact physician.
SKIN & EYE CONTACT - Wash with large amounts of water for 15 minutes.
INGESTION - Contact physician. Do not induce vomiting unless directed to do so by a physician.

Carcinogenicity - Not listed or regulated as a carcinogen.
Medical Conditions Aggravated By Exposure - None known.

PERSONAL PROTECTION RECOMMENDATIONS

Protective gloves, goggles and mechanical ventilation in confined areas.
Wash hands thoroughly after handling and before eating or smoking.

PRECAUTIONS FOR SAFE HANDLING AND USE

Spill Procedure - Keep out of sewer systems. Dike and cover spill with absorbent material. Sweep or shovel up.
Waste Disposal Method - May be incinerated or landfilled in accordance with local, state and federal regulations.
Storage Precautions - Do not allow to freeze or store in direct sunlight or at temperatures above 90F for prolonged periods.

SHIPPING INFORMATION

Not regulated.