

MATERIAL SAFETY DATA SHEET**MER-KRETE LATEX 200**

SUPPLIER	Mer-Krete Systems, a division of ParexLahabra 501 Van Ness Avenue Torrance, CA 90501	CONTACT	Gary Linza
		PHONE	310.320.1880
		DATE	08.25.99

INGREDIENTS	CAS NUMBER	OSHA	ACGIH
Styrene/Butadiene Polymer	9003-55-8	N/A	N/A
Water	7732-18-5	N/A	N/A

PHYSICAL/CHEMICAL CHARACTERISTICS			
Boiling Point - 100C	Freezing Point - 0C	Vapor Density - 17.5 @ 20C	Specific Gravity - 1.00
Solubility in Water - Soluble in all proportions		Appearance - Milky white liquid	Odor - Sweet smelling

FIRE & EXPLOSION HAZARDS			
Flash Point - N/A Special Fire Fighting Procedures - Wear self-contained breathing apparatus.			
Unusual Fire & Explosion Hazards - Black smoke, noxious gases may be generated if material ignites after water boils off.			

REACTIVITY DATA			
Stability-Stable	Materials to Avoid - None	Hazardous Decomposition or Byproducts - None	
Hazardous Polymerization - Will not occur			

HEALTH HAZARD DATA			
Routes of Entry - Inhalation, Skin Contact, Eye Contact, Ingestion			
INHALATION - May cause irritation of the nose and throat.			
SKIN CONTACT - Prolonged or repeated exposure may cause slight skin irritation.			
EYE CONTACT - May cause pain and irritation depending on duration of contact.			
INGESTION - May cause nausea, vomiting, abdominal pain. Toxicity is considered to be low.			
First Aid Procedures			
INHALATION - Remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen. Contact physician.			
SKIN & EYE CONTACT - Wash with large amounts of water for 15 minutes.			
INGESTION - Contact physician. Do not induce vomiting unless directed to do so by a physician.			
Carcinogenicity - Not listed or regulated as a carcinogen.			
Medical Conditions Aggravated By Exposure - None known.			

PERSONAL PROTECTION RECOMMENDATIONS			
Protective gloves, goggles and mechanical ventilation in confined areas.			
Wash hands thoroughly after handling and before eating or smoking.			

PRECAUTIONS FOR SAFE HANDLING AND USE			
Spill Procedure - Keep out of sewer systems. Dike and cover spill with absorbent material. Sweep or shovel up.			
Waste Disposal Method - May be incinerated or landfilled in accordance with local, state and federal regulations.			
Storage Precautions - Do not allow to freeze or store in direct sunlight or at temperatures above 90F for prolonged periods.			

SHIPPING INFORMATION			
Not regulated.			